

ILLuminec Led

Led Tube 15T 155lm/W met interne driver, single sided power

Voltage	AC100V-277V 50/64Hz
PF	>0.94
Led type	Epistar 2835
Aantal Led's	60-6W / 96-9W / 144-12W / 168-16W 192-18W/ 276-25W
Luminus efficiency	163lm/W (6000K) 155lm/W (5000K) 150lm/W (4000K)
CCT	4000 - 5000 - 6000K
CRI	>80
Openingshoek	160°
Cover	Frosted
Lamphouder	G13
Levensduur	50 000 u
Garantie	5 jaar
Voor omgevingstemp	-35 + 55°C
Temp tijdens opslag	-40 + 80°C
IP waarde	IP44



ILL15T60-6W840	60 cm 6 Watt 4000K 900lm
ILL15T60-6W850	60 cm 6 Watt 5000K 930lm
ILL15T60-6W860	60 cm 6 Watt 6000K 978m
ILL15T60-9W840	60 cm 9 Watt 4000K 1350lm
ILL15T60-9W850	60 cm 9 Watt 5000K 1395lm
ILL15T60-9W860	60 cm 9 Watt 6000K 1467m
ILL15T120-12W840	120 cm 12 Watt 4000K 1800lm
ILL15T120-12W850	120 cm 12 Watt 5000K 1860lm
ILL15T120-12W860	120 cm 12 Watt 6000K 1956lm
ILL15T120-18W840	120 cm 18 Watt 4000K 2700lm
ILL15T120-18W850	120 cm 18 Watt 5000K 2790lm
ILL15T120-18W860	120 cm 18 Watt 6000K 2934lm
ILL15T150-16W840	150 cm 16 Watt 4000K 2400lm
ILL15T150-16W850	150 cm 16 Watt 5000K 2480lm
ILL15T150-16W860	150 cm 16 Watt 6000K 2608lm
ILL15T150-25W840	150 cm 25 Watt 4000K 3750lm
ILL15T150-25W850	150 cm 25 Watt 5000K 3875lm
ILL15T150-25W860	150 cm 25 Watt 6000K 4075lm

ILL-START LEDSTARTER

